



Watts	Bulb	Base	Order Code	Description	Pkg. Qty.	Apprx. Hours	Burning Position	Apprx. Initial Lumen	Apprx. Mean Lumen	Kelvin Temp.	CRI
-------	------	------	------------	-------------	-----------	--------------	------------------	----------------------	-------------------	--------------	-----

**SAFETY COATED METAL HALIDE**

175	ED28	Mog	<b>80311</b>	MH175/TC HI-TEMP	6	20000	UNIVERSAL	15000	11000	4000	65
250	ED28	Mog	<b>80310</b>	MH250/TC HI-TEMP	6	20000	UNIVERSAL	20500	17000	4000	65
400	ED37	Mog	<b>06087</b>	MH400/TC HI-TEMP	6	20000	UNIVERSAL	36000	28800	4000	65

**BRITE LUX METAL HALIDE RETROFIT FOR HPS**

250	ED28	Mog	<b>30016</b>	MS250/BU/LU	12	20000	BU ± 15	20500	15400	4000	65
400	ED28	Mog	<b>30018</b>	MS400/C/BU/LU	6	20000	BU ± 15	36000	28000	4000	65
	ED37	Mog	<b>30014</b>	MS400/BU/LU	6	20000	BU ± 15	40000	32000	4000	65
	ED28	Mog	<b>30013</b>	MH400/U/LU/ED28	12	20000	UNIVERSAL	20000	31000	4000	65

**HIGH PRESSURE SODIUM**

35	E17	Med	<b>20101</b>	LU35/MED	Clear	20	24000	UNIVERSAL	2250	2025	2200	21
50	E17	Med	<b>20102</b>	LU50/MED	Clear	20	24000	UNIVERSAL	4000	3600	2200	21
	ET23 1/2	Mog	<b>20002</b>	LU50/MOG	Clear	20	24000	UNIVERSAL	4000	3600	2200	21
70	E17	Med	<b>20103</b>	LU70/MED	Clear	20	24000	UNIVERSAL	6300	5670	2200	21
	ED23 1/2	Mog	<b>20003</b>	LU70/MOG	Clear	20	24000	UNIVERSAL	6300	5670	2200	21
100	E17	Med	<b>20104</b>	LU100/MED	Clear	20	24000	UNIVERSAL	9500	8550	2200	21
	ET23 1/2	Mog	<b>20004</b>	LU100/MOG	Clear	20	24000	UNIVERSAL	9500	8550	2200	21
150	E17	Med	<b>20105</b>	LU150/55/MED	Clear	20	24000	UNIVERSAL	16000	14400	2200	21
	ET23 1/2	Mog	<b>20005</b>	LU150/55/MOG	Clear	20	24000	UNIVERSAL	16000	14400	2200	21
250	ET18	Mog	<b>20050</b>	LU250/T/MOG	Clear	12	24000	UNIVERSAL	28000	25200	2200	21
400	ET18	Mog	<b>20051</b>	LU400/T/MOG	Clear	12	24000	UNIVERSAL	50000	45000	2200	21
1000	E25	Mog	<b>60318</b>	LU1000/MOG	Clear	6	24000	UNIVERSAL	140000	126000	2200	21

**SAFETY COATED HIGH PRESSURE SODIUM**

250	T15	Mog	<b>06081</b>	LU250/T/TC HI-TEMP	12	24000	UNIVERSAL	28000	25200	2200	21
400	T15	Mog	<b>06080</b>	LU400/T/TC HI-TEMP	12	24000	UNIVERSAL	50000	45000	2200	21

**MERCURY VAPOR**

100	A23	Med	<b>60324</b>	H38MP-100DX/MED	24	24000	UNIVERSAL	4300	3400	3700	45
	ED23 1/2	Mog	<b>60328</b>	H38JA-100/DX/MOG	12	24000	UNIVERSAL	4400	3400	3700	45
175	ED28	Mog	<b>60326</b>	H39KC-175/DX/MOG	12	24000	UNIVERSAL	7900	7400	3700	45
		Mog	<b>60325</b>	H39KB-175/CL/MOG	12	24000	UNIVERSAL	8500	7600	6800	20
250	ED28	Mog	<b>60327</b>	H37KC-250/DX/MOG	12	24000	UNIVERSAL	13000	10700	3700	45
400	ED37	Mog	<b>60239</b>	H33GL-400/DX/MOG	6	24000	UNIVERSAL	23000	19100	3700	45
1000	BT56	Mog	<b>60286</b>	H36GW-1000/DX/MOG	6	24000	UNIVERSAL	63000	47500	3700	45

\* HI-TEMP lamps should not be used as heat or brooder lamps for poultry or birds.