



4 Pin High Lumen



Spiral



CF9/BL



Micro Lynx F

Watts	Base	Order Code	Description	Pkg. Qty.	Lth. (in.)	O.D. (in.)	Apprx. Hours	Apprx. Initial Lumen	Min. Starting Temp.	Apprx. Incandes. Equivalent	CRI	Kelvin Temp.
-------	------	------------	-------------	-----------	------------	------------	--------------	----------------------	---------------------	-----------------------------	-----	--------------

LYNX L 4 PIN BASE HIGH LUMEN

18	2G11	25670	FT18LD/830	10	9		12000	1250		75W	82	3000
		25672	FT18LD/835	10	9		12000	1250		75W	82	3500
		25671	FT18LD/841	10	9		12000	1250		75W	82	4100
24	2G11	25675	FT24LD/830	10	12.9		12000	1800		100W	82	3000
		25677	FT24LD/835	10	12.9		12000	1800		100W	82	3500
		25676	FT24LD/841	10	12.9		12000	1800		100W	82	4100
36	2G11	25680	FT36LD/830	10	16.6		12000	2900		200W	82	3000
		25682	FT36LD/835	10	16.6		12000	2900		200W	82	3500
		25681	FT36LD/841	10	16.6		12000	2900		200W	82	4100
40	2G11	25685	FT40LD/830	10	21.1		20000	3150		250W	82	3000
		25687	FT40LD/835	10	21.1		20000	3150		250W	82	3500
		25686	FT40LD/841	10	21.1		20000	3150		250W	82	4100
55	2G11	25690	FT55LD/830	10	21.1		12000	4800		300W	82	3000
		25689	FT55LD/835	10	21.1		12000	4800		300W	82	3500
		25691	FT55LD/841	10	21.1		12000	4800		300W	82	4100

MICRO-LYNX F

6	GX53	55231	Micro-Lynx/830	20			10000	220			85	4100
		55232	Micro-Lynx/841	20			10000	220			85	3000

MINI LYNX INTEGRATED SPIRAL COMPACT FLUORESCENT *

11	Med	26150	11MLS/827	10	4.80	1.80	8000	700	0°F	40W	82	2700
		26152	11MLS/841	10	4.80	1.80	8000	700	0°F	40W	82	4100
		26153	11MLS/850	10	4.80	1.80	8000	700	0°F	40W	82	5000
		26140	11LG/827 Globe	12	5.25	3.13	8000	550	0°F	40W	82	2700
15	Med	26154	15MLS/827	10	5.25	1.80	8000	900	0°F	60W	82	2700
		26156	15MLS/841	10	5.25	1.80	8000	900	0°F	60W	82	4100
		26157	15MLS/850	10	5.25	1.80	8000	900	0°F	60W	82	5000
		26141	15LG/827 Globe	12	6.00	3.75	8000	830	0°F	60W	82	2700
		26142	15LR30/827 Reflector	6	6.30	3.75	8000	660	0°F	65W	82	2700
20	Med	26158	20MLS/827	10	5.70	2.31	8000	1200	0°F	75W	82	2700
		26160	20MLS/841	10	5.70	2.31	8000	1200	0°F	75W	82	4100
		26161	20MLS/850	60	5.70	2.31	8000	1200	0°F	75W	82	5000
		26143	20LR40/827 Reflector	6	6.85	5.0	8000	980	0°F	100W	82	2700
25/26	Med	26162	25MLS/827	10	6.25	2.31	8000	1650	0°F	100W	82	2700
		26164	25MLS/841	10	6.25	2.31	8000	1650	0°F	100W	82	4100
		26165	25MLS/850	10	6.25	2.31	8000	1650	0°F	100W	82	5000

BLACKLIGHT

9	G23	26088	CF9BL/350	50	6.5		10000					
---	-----	--------------	-----------	----	-----	--	-------	--	--	--	--	--

* Use in Recessed High Hats could affect average life.