





Nom. Watts	Nom. Length (in.)	Base	Bulb	Order Code	Description	Pkg. Qty.	Rated Life (hours)	Initial Lumens	Design Lumens	Kelvin Temp.	CRI	
<b>T-8 HIGH PERFORMANCE</b>												
28	48	Med Bi Pin	T8	<b>01900</b>	F28T8/830/ES	Terra-Lux Energy Saver	25	24000	2775	2635	3000	85
				<b>01901</b>	F28T8/835/ES	Terra-Lux Energy Saver	25	24000	2775	2635	3500	85
				<b>01902</b>	F28T8/841/ES	Terra-Lux Energy Saver	25	24000	2775	2635	4100	85
				<b>01903</b>	F28T8/850/ES	Terra-Lux Energy Saver	25	24000	2775	2635	5000	85
32	48	Med Bi Pin	T8	<b>01920</b>	F32T8/835/HL	Terra-Lux High Lumen	25	24000	3100	2915	3500	85
				<b>01921</b>	F32T8/841/HL	Terra-Lux High Lumen	25	24000	3100	2915	4100	85
				<b>01923</b>	F32T8/850/HL	Terra-Lux High Lumen	25	24000	3100	2915	5000	85
				<b>01711</b>	F32T8/730	Terra-Lux	25	20000	2850	2710	3000	75
				<b>01712</b>	F32T8/735	Terra-Lux	25	20000	2850	2710	3500	75
				<b>01713</b>	F32T8/741	Terra-Lux	25	20000	2850	2710	4100	75
				<b>01911</b>	F32T8/741	Terra-Lux	6	20000	2850	2710	4100	75
				<b>01705</b>	F32T8/750	Terra-Lux	25	20000	2850	2710	5000	75
				<b>01708</b>	F32T8/830	Terra-Lux	25	24000	3050	2895	3000	85
				<b>01709</b>	F32T8/835	Terra-Lux	25	24000	3050	2895	3500	85
				<b>01707</b>	F32T8/841	Terra-Lux	25	24000	3050	2895	4100	85
				<b>01704</b>	F32T8/850	Terra-Lux	25	24000	3050	2895	5000	85
<b>01737</b>	F32T8/865	Terra-Lux	25	24000	3050	2895	6500	85				
58	60	Med Bi Pin	T8	<b>01740</b>	F58T8/835		25	15000	5200	4840	3500	85
				<b>01741</b>	F58T8/841		25	15000	5200	4840	4100	85
70	72	Med Bi Pin	T8	<b>01751</b>	F70T8/841		25	15000	6000	5580	4100	85
				<b>51752</b>	F70T8/860		25	15000	6000	5580	6000	85
96	96	Single Pin	T8	<b>60453</b>	F96T8/730		24	15000	5700	5190	3000	75
				<b>60439</b>	F96T8/735		24	15000	5700	5190	3500	75
				<b>60438</b>	F96T8/741		24	15000	5700	5190	4100	75
<b>T-8 STANDARD</b>												
14	15	Med Bi Pin	T8	<b>60410</b>	F14T8/CW	Cool White	25	9000	710	590	4100	62
15	18	Med Bi Pin	T8	<b>19001</b>	F15T8/CW	Cool White	6	10000	870	765	4100	62
				<b>01714</b>	F15T8/CW	Cool White	25	10000	870	765	4100	62
				<b>01715</b>	F15T8/D	Daylight	25	10000	870	765	6500	76
				<b>60416</b>	F15T8/D	Daylight	112	10000	870	765	6500	76
30	36	Med Bi Pin	T8	<b>17923</b>	F30T8/CW	Cool White	6	7500	2200	2000	4100	62
				<b>60412</b>	F30T8/CW	Cool White	30	7500	2200	2000	4100	62
				<b>60414</b>	F30T8/D	Daylight	25	7500	820	655	6500	76
32	48	Med Bi Pin	T8	<b>17944</b>	F32T8/EXCELLA		30	20000	2650	2895	5765	91
<b>T10</b>												
40	48	Med Bi Pin	T10	<b>30539</b>	F40T10/4100		25	24000	3700	3300	4100	88
				<b>30540</b>	F40T10/5000		25	24000	3700	3300	5000	88
<b>T-12 ENERGY SAVER</b>												
34	48	Med Bi Pin	T12	<b>30530</b>	F34T12/CW/ES	Terra-Lux	30	20000	2650	2300	4100	62
				<b>30532</b>	F34T12/CW/ES/Overwrap	Terra-Lux	30	20000	2650	2300	4100	62
				<b>30534</b>	F34T12/CW/ES/Strong Box	Terra-Lux	6	20000	2650	2300	4100	62
				<b>30531</b>	F34T12/CW/ES/Strong Box	Terra-Lux	30	20000	2650	2300	4100	62
				<b>30537</b>	F34T12/WWW/ES	Terra-Lux	30	20000	2700	2350	3000	53
				<b>30576</b>	F34T12/WWW/ES/Overwrap	Terra-Lux	30	20000	2700	2350	3000	53
				<b>30535</b>	F34T12/WWW/ES/Strong Box	Terra-Lux	6	20000	2700	2350	3000	53
				<b>30538</b>	F34T12/WWW/ES/Strong Box	Terra-Lux	30	20000	2700	2350	3000	53
<b>18120</b>	F40T12/LIGHT-WHITE/ES	Light White	6	20000	2850	2500	4100	62				



Nom. Watts	Nom. Length (in.)	Base	Bulb	Order Code	Description	Pkg. Qty.	Rated Life (hours)	Initial Lumens	Design Lumens	Kelvin Temp.	CRI	
<b>T-12 ENERGY SAVER</b>												
60	96	Single Pin	T12	<b>30544</b>	F96T12/CW/ES	Terra-Lux	6	12000	5400	4750	4110	62
				<b>30545</b>	F96T12/CW/ES	Terra-Lux	15	12000	5400	4750	4100	62
				<b>30543</b>	F96T12/CW/ES/Overwrap	Terra-Lux	15	12000	5400	4750	4100	62
				<b>30585</b>	F96T12/CW/ES/Strong Box	Terra-Lux	6	12000	5400	4750	4100	62
				<b>18053</b>	F96T12/CW/ES/Strong Box	Terra-Lux	15	12000	5400	4750	4100	62
				<b>18116</b>	F96T12/CW/ES/TC	Toughcoat	6	12000	5400	4750	4018	62
				<b>18117</b>	F96T12/CW/ES/TC	Toughcoat	15	12000	5400	4750	4018	62
<b>T-12 STANDARD</b>												
14	15	Med Bi Pin	T12	<b>18187</b>	F14T12/CW	Cool White	30	9000	710	590	4100	62
15	18	Med Bi Pin	T12	<b>19002</b>	F15T12/CW	Cool White	6	9000	800	695	4100	62
				<b>60415</b>	F15T12/CW	Cool White	30	9000	800	695	4100	62
20	24	Med Bi Pin	T12	<b>19003</b>	F20T12/CW	Cool White	6	9000	1200	1050	4100	62
				<b>60418</b>	F20T12/CW	Cool White	30	9000	1200	1050	4100	62
30	36	Med Bi Pin	T12	<b>19004</b>	F30T12/CW	Cool White	6	18000	2250	1900	4100	62
				<b>60417</b>	F30T12/CW	Cool White	30	18000	2250	1900	4100	62
				<b>01761</b>	F30T12/DL	Daylight	25	18000	2250	1900	6500	76
40	48	Med Bi Pin	T12	<b>30561</b>	F40T12/CWX/Shoplite		30	20000	2250	1800	4100	89
				<b>30562</b>	F40T12/CWX/Strong Box	Cool White Deluxe	6	20000	2250	1800	4000	89
				<b>30563</b>	F40T12/CWX/Strong Box	Cool White Deluxe	30	20000	2250	1800	4100	89
				<b>18114</b>	F40T12/CWX/TC	Toughcoat	6	20000	2250	1800	4100	89
				<b>18115</b>	F40T12/CWX/TC	Toughcoat	30	20000	2250	1800	4100	89
				<b>30568</b>	F40T12/DL/DLX	Daylight Deluxe	30	20000	2675	2325	6500	84
				<b>30570</b>	F40T12/DL/DLX/Overwrap	Daylight Deluxe	30	20000	2675	2325	6500	84
				<b>30577</b>	F40T12/DL/DLX/Strong Box	Daylight Deluxe	30	20000	2675	2325	6500	84
				<b>30571</b>	F40T12/DL/DX/Strong Box	Daylight Deluxe	30	20000	2675	2325	6500	84
				<b>18029</b>	F40T12/EXCELLA		30	20000	2150	1900	5765	91
				<b>18031</b>	F40T12/EXCELLA/Overwrap		30	20000	2150	1900	5765	91
				<b>18030</b>	F40T12/EXCELLA/Strong Box		6	20000	2150	1900	5765	91
				<b>18028</b>	F40T12/EXCELLA/Strong Box		30	20000	2150	1900	5765	91
				<b>18037</b>	F40T12/SNO/DLX	Snow White Deluxe	30	20000	2400	2000	5100	82
				<b>18039</b>	F40T12/SNO/DLX/Overwrap	Snow White Deluxe	30	20000	2400	2000	5100	82
				<b>18038</b>	F40T12/SNO/DLX/Strong Box	Snow White Deluxe	30	20000	2400	2000	5100	82
				<b>01774</b>	F40T12/730		25	20000	3200	2750	3000	75
				<b>01771</b>	F40T12/735		25	20000	3200	2750	3500	75
				<b>01782</b>	F40T12/741		25	20000	3200	2750	4100	75
				<b>01775</b>	F40T12/750		25	20000	3200	2750	5000	75
75	96	Single Pin	T12	<b>18072</b>	F96T12/EXCELLA		15	12000	5370	4720	5765	91
				<b>18073</b>	F96T12/EXCELLA/Overwrap		15	12000	5370	4720	5765	91
<b>T-12 SLIM LINE INSTANT START</b>												
39	48	Single Pin	T12	<b>30525</b>	F48T12/CW		30	9000	2900	2600	4100	62
				<b>30527</b>	F48T12/CW/Strong Box		30	9000	2900	2600	4100	62
50	60	Single Pin	T12	<b>18122</b>	F60T12/CW	Cool White	6	12000	3700	3450	4100	62
				<b>18123</b>	F60T12/CW	Cool White	15	12000	3700	3450	4100	62
56	72	Single Pin	T12	<b>30528</b>	F72T12/CW	Cool White	6	12000	4450	3900	4100	62
				<b>18048</b>	F72T12/CW	Cool White	15	12000	4450	3900	4100	62
75	96	Single Pin	T12	<b>30565</b>	F96T12/DL/DLX		15	12000	4500	3950	6500	84
				<b>30567</b>	F96T12/DL/DLX/Overwrap		15	12000	4500	3950	6500	84
				<b>18076</b>	F96T12/SN-WHT/DLX		15	12000	7165	6230	5100	82



Nom. Watts	Nom. Length (in.)	Base	Bulb	Order Code	Description	Pkg. Qty.	Rated Life (hours)	Initial Lumens	Design Lumens	Kelvin Temp.	CRI	
<b>HIGH OUTPUT</b>												
60	48	RDC	T12	<b>18061</b>	F48T12/CW/HO	6	12000	4050	3500	4100	62	
				<b>30551</b>	F48T12/CW/HO	15	12000	4050	3500	4100	62	
				<b>30552</b>	F48T12/CW/HO/Strong Box	15	12000	4050	3500	4100	62	
				<b>18725</b>	F48T12/CW/HO/TC	Toughcoat	15	12000	4050	3500	4100	62
				<b>00301</b>	F48T12/DL/HO		30	12000	3400	3000	6500	76
75	60	RDC	T12	<b>18194</b>	F60T12/CW/HO	6	12000	5200	4500	4100	62	
				<b>18193</b>	F60T12/CW/HO	15	12000	5200	4500	4100	62	
				<b>18727</b>	F60T12/CW/HO/TC	Toughcoat	15	12000	5200	4500	4100	62
80	64	RDC	T12	<b>30592</b>	F64T12/D/HO	15	12000	4900	4250	6500	76	
85	72	RDC	T12	<b>00340</b>	F72T12/CW/HO	15	12000	6350	5000	4100	62	
				<b>18729</b>	F72T12/CW/HO/TC	Toughcoat	15	12000	6350	5000	4100	62
				<b>00341</b>	F72T12/D/HO	15	12000	6350	5000	4100	62	
98	96	RDC	T12	<b>30547</b>	F96T12/CW/HO/ES	15	12000	8000	6900	4100	62	
				<b>30548</b>	F96T12/CW/HO/ES/Overwrap	15	12000	8000	6900	4100	62	
110	96	RDC	T12	<b>01590</b>	F96T12/CW/HO-0	15	12000	8800	7650	4100	62	
				<b>30555</b>	F96T12/CW/HO-0/Overwrap	15	12000	8800	7650	4100	62	
				<b>18107</b>	F96T12/CW/HO-0/Strong Box	6	12000	8800	7650	4100	62	
				<b>30581</b>	F96T12/CW/HO-0/Strong Box	15	12000	8800	7650	4100	62	
				<b>18731</b>	F96T12/CW/HO/TC	Toughcoat	15	12000	8800	7650	4100	62
				<b>18693</b>	F96T12/DL/DLX/HO	15	12000	7800	6788	6500	75	
				<b>01580</b>	F96T12/DL/HO-0	15	12000	7800	6788	6500	75	
				<b>18082</b>	F96T12/SNO/DLX/HO	15	12000	7165	6230	5100	82	
<b>VERY HIGH OUTPUT</b>												
215	96	RDC	T12	<b>30558</b>	F96T12/CW/VHO	Very High Output	15	12000	15200	10700	4100	62
				<b>30559</b>	F96T12/CW/VHO	Very High Output	30	12000	15200	10700	4100	62
<b>U-BENT T-8 6 INCH</b>												
32	22 1/2	Med Bi Pin	T8	<b>30470</b>	FB32T8/730/6	Terra-Lux	20	24000	2750	2475	3000	75
				<b>30472</b>	FB32T8/735/6	Terra-Lux	20	24000	2750	2475	3500	75
				<b>30471</b>	FB32T8/741/6	Terra-Lux	20	24000	2750	2475	4100	75
				<b>30478</b>	FB32T8/750/6	Terra-Lux	20	24000	2750	2475	5000	75
				<b>30475</b>	FB32T8/830/6	Terra-Lux	20	24000	2900	2610	3000	85
				<b>30476</b>	FB32T8/835/6	Terra-Lux	20	24000	2900	2610	3500	85
				<b>30477</b>	FB32T8/841/6	Terra-Lux	20	24000	2900	2610	4100	85
				<b>30479</b>	FB32T8/850/6	Terra-Lux	20	24000	2900	2610	5000	85
<b>U-BENT T-8 1-5/8 INCH</b>												
31	22 1/2	Med Bi Pin	T8	<b>30468</b>	FB31T8/835 1-5/8		12	20000	2725	2507	3500	82
31	22 1/2	Med Bi Pin	T8	<b>30469</b>	FB31T8/841 1-5/8		12	20000	2725	2507	4100	82
<b>U-BENT T-12</b>												
34	22 1/2	Med Bi Pin	T12	<b>30473</b>	FB34CW/ES/6		12	18000	2400	2000	3000	62
				<b>30480</b>	FB34CW/ES/6/Overwrap		12	18000	2400	2000	4100	62
				<b>30474</b>	FB40WW/ES/6		12	18000	2400	2000	3000	53
				<b>18047</b>	FB40/EXCELLA/6		6	18000	2150	1900	5765	91