

Med Bi Pin

RDC

T-8 Medium Bi Pin U-Bent Lamp

T-12 Medium Bi Pin U-Bent Lamp (6")

Nom. Watts	Nom. Length (in.)	Base	Bulb	Order Code	Description	Pkg. Qty.	Rated Life (hours)	Initial Lumens	Design Lumens	Kelvin Temp.	CRI
------------	-------------------	------	------	------------	-------------	-----------	--------------------	----------------	---------------	--------------	-----

**HIGH OUTPUT**

60	48	RDC	T12	<b>18061</b>	F48T12/CW/HO	6	12000	4050	3500	4100	62	
				<b>30551</b>	F48T12/CW/HO	15	12000	4050	3500	4100	62	
				<b>30552</b>	F48T12/CW/HO/Strong Box	15	12000	4050	3500	4100	62	
				<b>18725</b>	F48T12/CW/HO/TC	Toughcoat	15	12000	4050	3500	4100	62
				<b>00301</b>	F48T12/DL/HO	30	12000	3400	3000	6500	76	
75	60	RDC	T12	<b>18194</b>	F60T12/CW/HO	6	12000	5200	4500	4100	62	
				<b>18193</b>	F60T12/CW/HO	15	12000	5200	4500	4100	62	
				<b>18727</b>	F60T12/CW/HO/TC	Toughcoat	15	12000	5200	4500	4100	62
80	64	RDC	T12	<b>30592</b>	F64T12/D/HO	15	12000	4900	4250	6500	76	
85	72	RDC	T12	<b>00340</b>	F72T12/CW/HO	15	12000	6350	5000	4100	62	
				<b>18729</b>	F72T12/CW/HO/TC	Toughcoat	15	12000	6350	5000	4100	62
				<b>00341</b>	F72T12/D/HO	15	12000	6350	5000	4100	62	
98	96	RDC	T12	<b>30547</b>	F96T12/CW/HO/ES	15	12000	8000	6900	4100	62	
				<b>30548</b>	F96T12/CW/HO/ES/Overwrap	15	12000	8000	6900	4100	62	
110	96	RDC	T12	<b>01590</b>	F96T12/CW/HO-0	15	12000	8800	7650	4100	62	
				<b>30555</b>	F96T12/CW/HO-0/Overwrap	15	12000	8800	7650	4100	62	
				<b>18107</b>	F96T12/CW/HO-0/Strong Box	6	12000	8800	7650	4100	62	
				<b>30581</b>	F96T12/CW/HO-0/Strong Box	15	12000	8800	7650	4100	62	
				<b>18731</b>	F96T12/CW/HO/TC	Toughcoat	15	12000	8800	7650	4100	62
				<b>18693</b>	F96T12/DL/DLX/HO	15	12000	7800	6788	6500	75	
				<b>01580</b>	F96T12/DL/HO-0	15	12000	7800	6788	6500	75	
<b>18082</b>	F96T12/SNO/DLX/HO	15	12000	7165	6230	5100	82					

**VERY HIGH OUTPUT**

215	96	RDC	T12	<b>30558</b>	F96T12/CW/VHO	Very High Output	15	12000	15200	10700	4100	62
				<b>30559</b>	F96T12/CW/VHO	Very High Output	30	12000	15200	10700	4100	62

**U-BENT T-8 6 INCH**

32	22 1/2	Med Bi Pin	T8	<b>30470</b>	FB32T8/730/6	Terra-Lux	20	24000	2750	2475	3000	75
				<b>30472</b>	FB32T8/735/6	Terra-Lux	20	24000	2750	2475	3500	75
				<b>30471</b>	FB32T8/741/6	Terra-Lux	20	24000	2750	2475	4100	75
				<b>30478</b>	FB32T8/750/6	Terra-Lux	20	24000	2750	2475	5000	75
				<b>30475</b>	FB32T8/830/6	Terra-Lux	20	24000	2900	2610	3000	85
				<b>30476</b>	FB32T8/835/6	Terra-Lux	20	24000	2900	2610	3500	85
				<b>30477</b>	FB32T8/841/6	Terra-Lux	20	24000	2900	2610	4100	85
				<b>30479</b>	FB32T8/850/6	Terra-Lux	20	24000	2900	2610	5000	85

**U-BENT T-8 1-5/8 INCH**


31	22 1/2	Med Bi Pin	T8	<b>30468</b>	FB31T8/835 1-5/8		12	20000	2725	2507	3500	82
31	22 1/2	Med Bi Pin	T8	<b>30469</b>	FB31T8/841 1-5/8		12	20000	2725	2507	4100	82

**U-BENT T-12**

34	22 1/2	Med Bi Pin	T12	<b>30473</b>	FB34CW/ES/6		12	18000	2400	2000	3000	62
				<b>30480</b>	FB34CW/ES/6/Overwrap		12	18000	2400	2000	4100	62
				<b>30474</b>	FB40WW/ES/6		12	18000	2400	2000	3000	53
				<b>18047</b>	FB40/EXCELLA/6		6	18000	2150	1900	5765	91



Med Bi Pin



T9 Circle Line

Nom. Watts	Nom. Length (in.)	Base	Bulb	Order Code	Description	Pkg. Qty.	Rated Life (hours)	Initial Lumens	Design lumens	Kelvin Temp.	CRI
<b>CIRCLINE</b>											
20	6 1/2 (OD)	4 Pin	T9	<b>60424</b>	FC6T9/CW	12	12000	800	590	4100	62
22	8 1/4 (OD)	4 Pin	T9	<b>00450</b>	FC8T9/CW	12	12000	1050	775	4100	62
32	12 (OD)	4 Pin	T9	<b>00452</b>	FC12T9/CW	12	12000	1800	1495	4100	62
40	16 (OD)	4 Pin	T9	<b>00453</b>	FC16T9/CW	12	12000	2750	2350	4100	62

### BLACKLIGHT

15	18	Med Bi Pin	T8	<b>01800</b>	F15T8/BL350	25	10000				
				<b>01802</b>	F15T8/BL368	25	10000				
				<b>01805</b>	F15T8/BL350/TC	Toughcoat	25	10000			
				<b>11800</b>	F15T8 BLACKLIGHT BLUE		25	10000			
20	24	Med Bi Pin	T12	<b>01803</b>	F20T12/BL350	25	9000				
				<b>01807</b>	F20T12/BL350/TC	Toughcoat	25	9000			
				<b>11801</b>	F20T12 BLACKLIGHT BLUE		6	9000			
30	36	Med Bi Pin	T8	<b>01804</b>	F30T8/BL350	25	7500				
40	48	Med Bi Pin	T10	<b>18689</b>	F40T10 BLACKLIGHT BLUE	10	20000				
40	48	Med Bi Pin	T12	<b>01801</b>	F40T12/BL350	25	20000				
				<b>01809</b>	F40T12/BL368	25					
				<b>18118</b>	F40T12/BL350/TC	Toughcoat	25	20000			
				<b>11802</b>	F40T12 BLACKLIGHT BLUE	6	10000				



Mini Bi Pin



Med Bi Pin

Watts	Bulb	Base	Order Code	Description	Wave Length (nm)	Pkg. Qty.	Length (in.)	Apprx. Hours	Lamp Current (A)	U.V. Output (W)
<b>GERMICIDAL LAMPS</b>										
8	T5	Mini Bi Pin	<b>00501</b>	G8T5	253.7	50	12	6000	.170	2.5
10	T5	Med Bi Pin	<b>00504</b>	G10T5/L	253.7	25	14 1/2	9000	.425	5.3
15	T8	Med Bi Pin	<b>00502</b>	G15T8	253.7	20	18	6000	.300	4.8
25	T8	Med Bi Pin	<b>00505</b>	G25T8	253.7	20	18	6000	.600	6.9
30	T8	Med Bi Pin	<b>00503</b>	G30T8	253.7	10	36	6000	.355	11.6
36	T5	Single Pin	<b>00506</b>	G36T5/L	253.7	10	33	9000	.425	16

Germicidal lamps efficiently emit a large amount of Ultraviolet rays, 253.7 nanometers, which have excellent germicidal effect. They are primarily useful for sterilization of air, the surfaces of various materials and water or other liquids.

Warning: The radiation of Germicidal lamps is harmful to eyes and skin. Protect them against the Ultraviolet rays.